

# athena®

## Multimedia Modular Rollabout



### Versatile

Athena is a professional video conferencing system suitable for conference rooms of any size with the added advantage of interchangeable modules

### Superior Quality Audio and Video

High quality audio and video coding guarantees flawless conversation and excellent visual communication

### Elegant and Stylish Design

Thanks to the exclusive design created by Michele De Lucchi, Athena transforms any space into an elegant professional video communications environment



Versatile, flexible, light-weight: specifically created with a system of interchangeable modules, Athena satisfies the requirements of each individual client. From the selection of set tops and monitors, to the choice of materials and colours, Athena offers the possibility to create an exclusive video communications environment, where high-technological content is exalted by elegant design from the architectural studio aMDL.

### Customizable

Available in a variety of versions according to the size of the monitor and type of integrated system (SD or HD), Athena provides the opportunity to customize your video communication environment by combining material and colours to suit individual taste and style.

### Real-time Collaboration

Thanks to the "Continuous Presence" function, Athena can connect up to 9 sites in mixed mode (IP and ISDN) depending on the type of MCU (Multipoint Conferencing Unit) integrated in the codec chosen for the system.

### User Interface

Multi-lingual GUI with user selectable graphic layout and colour choice.



**Supported set-top and codecs**

- Vega X3/X5/X7
- Vega X7r

	Type of System	Voice Tracking	Network interfaces	Audio/Video interfaces	MCU*
Vega X3	SD	no	2xLAN; 1BRI; max 4 BRI	4 video; 5 audio	up to 4 sites
Vega X5	SD	yes	2xLAN; 3BRI; max 6 BRI or 1PRI or Leased	10 video; 7 audio	up to 9 sites
Vega X7	HD	no	2xLAN; max 6BRI or 1PRI or Leased	13 video; 9 audio	up to 9 sites
Vega X7r	HD	no	2xLAN; 3BRI; max 6 BRI or 1PRI or Leased	13 video; 9 audio	up to 9 sites

\* Option

**Monitor**

- Possibility to integrate various models of Monitor, from 32" up to 52"
- Dual monitor 32"
- PAL or NTSC format
- PIP and PAP functions

**Supported standards**

- ITU-T H.320 ISDN
- ITU-T H.323 IP networks
- IETF-SIP (RFC3261) IP networks
- PPPoE
- Video H.261, H.263+, H.264, H.239, H.241
- Audio G.711, G.728, G.722, G.722.1, G.722.1 Annex C (v11), MPEG4 AAC-LD
- Data T.120
- LDAP H.350
- MCU compatibility H.243, H.231

**Video**

- Frame rate 15 fps @ 56 - 128 kbps  
30 fps @ 168 kbps - 4 Mbps
- Video resolution 720p 1280 x 720 pixels (only with X7/X7r)  
4CIF 704 x 576 pixels  
FCIF 352 x 288 pixels  
QCIF 176 x 144 pixels  
4CIF 704 x 576 pixels for still images (Annex D H.261)  
4SIF 704 x 480 pixels  
SIF 352 x 240 pixels  
QSIF 176 x 120 pixels  
4SIF 704 x 480 pixels for still images (H.261 Annex D)  
Up to 1024 x 768 pixels over XGA in H.263
- Remote camera control H.281 (H.320 - H.323)

**Audio**

- | Audio           | Band          | Bit rate      |
|-----------------|---------------|---------------|
| G.711           | 300 ÷ 3400 Hz | 48/56/64 kbps |
| G.722           | 50 ÷ 7000 Hz  | 48/56/64 kbps |
| G.722.1         | 50 ÷ 7000 Hz  | 24/32 kbps    |
| G.722.1 Annex C | 50 ÷ 14000 Hz | 24/32/48 kbps |
| G.728           | 50 ÷ 3400 Hz  | 16 kbps       |
| AAC-LD          | 50 ÷ 14000 Hz | 48/56/64 kbps |

- Echo cancellation Full-duplex
- Automatic Gain Control (AGC)
- Automatic Noise Suppression
- Adaptive post filtering
- 2 loudspeakers 7W RMS

**Network Protocols**

- TELNET, HTTP, SNMP, DNS, DHCP, RTP/RTCP, TCP/UDP, ARP

**Network features**

- Differentiated Service (DIFFSERV), IP Precedence, IP Type of Service (ToS), Auto Gatekeeper Discovery, Clever Packets Management (AeCPM)

**User Interface**

- Multilingual on-screen graphic user interface: Italian, English, French, Spanish, German, Portuguese, Norwegian, Swedish, Russian, Czech, Hungarian, Polish, Finnish, Simplified Chinese, Traditional Chinese, Japanese, Korean
- Infrared remote control for full function control
- Contextual help
- Diagnostics and management functions
- Call progress monitoring
- Supports AMX™ or Crestron™
- Graphic user interface with user selectable layout and colour choice
- Web streaming function: UNICAST and MULTICAST compatible with QuickTime™

**Closed Captioning / Text Chat**

- T.140 text chat, available from Web

**Security**

- AES encryption standard H.233, H.234, H.235
- NIST Certified (National Institute of Standards & Technology)

**Web management**

All the configuration, call, diagnostics and management functions are accessible using the following web browsers: Microsoft® Internet Explorer™, Netscape Navigator™

**Remote Diagnostics and Management**

	Local	Web Browser	SNMP
Self test	Yes	Yes	Yes
Diagnostics	Yes	Yes	Yes
Configuration	Yes	Yes	Yes
Call	Yes	Yes	
Error tracking	Yes	Yes	Yes

**Integrated Presentation**

- Supported applications Microsoft® PowerPoint®
- Multimedia support T.120

**Dimensions**

- ATHENA
 

Width	90 cm (35.4")
Height	90 cm (35.4") (excluding monitor and camera)
Depth	70 cm (27.6")

**AETHRA® SpA**

via Matteo Ricci, 10  
 60126 Ancona (Italy)  
 Telephone +39.071.218981  
 Fax +39.071.887077  
 Video 1 +39.071.2189704  
 Video 2 +39.071.2189701

Beijing Hong Kong London Madrid  
 Mexico City Paris Miami São Paulo  
 Shanghai Shenzhen

Email: info.aethra@aethra.com  
**www.aethra.com**