

Hitachi Software PX Duo Interactive Overlay

Making plasma screens instantly interactive

Transform a plasma screen into a fully interactive, powerful presentation tool with no shadow or glare



Hitachi's PX Duo Interactive Overlay fits over an ordinary *plasma screen instantly turning it into a fully interactive device with pin-sharp resolution. With its touch-sensitive screen, large 55 or 65 inch diagonal display and its sleek bezel, the PX-Duo transforms your plasma into the ultimate feature-rich presentation tool. One that looks as good as it performs.

Ideal for teaching, corporate presentations and teleconferencing, the PX Duo uses existing StarBoard software with its powerful annotation tools, screen record capability, video annotation, PowerPoint integration and live collaboration. So you can share images, files, lesson plans and presentations with people using Hitachi interactive devices in other locations. It will even enable two people to input information simultaneously and the ability to operate the screen using both hands.

With the PX Duo you get interactivity with brilliant visuals, new levels of responsiveness, and all the benefits of live presenting and conferencing with none of the drawbacks.

*Bezel designed to fit Panasonic TH-50PF10EK and TH-6510EK screens only.

Dual inspiration, unlimited potential

HITACHI
Inspire the Next

PX-Duo at a glance:

Applications

- Teaching and lecturing
- Presentations
- Client meetings
- Seminars, shows
- Office-to-office conferencing/teleconferencing.

Key Benefits and Features

- Simplicity – control buttons that scroll through presentation pages, and mouse and pen control
- Slicker presenting – powerful StarBoard tools
- Flexibility – use electronic pen or a stylus pen (both supplied) or finger
- Peace of mind – three-year warranty
- Convenience – powered by single USB interface
- Fits 50" and 65" screens
- Bezel designed to fit Panasonic TH-50PF10EK and TH-6510EK screens only.



Specifications	PX-DUO-50	PX-DUO-65
Hardware Specifications		
Model No.:	AH00201	AH00204
Input Methods:	Infrared Image Sensor System	
Interface to Computer:	USB 1.1, 2.0	
Effective Screen Size:	50 Inches (1,106 mm (W) x 622mm (H))	65 Inches (1,434 mm (W) x 807mm (H))
Sampling Rate:	Approximately 100 points/sec	
Resolution:	Approximately 0.05 mm	
Accuracy:	Approximately ±1.5 mm	
Operating Specification:	5 – 35 Celsius, 20 – 80% Humidity without condensation	
Dimensions (w/o stand & PDP) (mm):	1,220(W) x 845(H) x 66(D)	1,556(W) x 1,041(H) x 66(D)
Weight (w/o stand & PDP) (kg):	Approx. 7kg	Approx. 9kg
Packing dimension (mm):	1,320(W) x 980(H) x 160(D)	1,674(W) x 1,175(H) x 160(D)
Packing weight (main unit):	Approx. 15kg	Approx. 19kg
Certificates:	VCCI Class B, FCC Class B, CE, UL	

Hitachi Software Engineering (UK) Limited
Interactive Media Solutions Division
Tel: +44 (0)207 246 6868
Fax: +44 (0)207 246 6860
Email: sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S
Interactive Media Solutions Division
Tel: +33 (0)153 827 600
Fax: +33 (0)153 827 619
Email: starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe AG
Interactive Media Solutions Division
Tel: +49 (0)30 8877 2600
Fax: +49 (0)30 8877 2610
Email: starboard@hitachisoft.de

www.hitachisoft-eu.com

Further information:

HITACHI
Inspire the Next